

Coast Guard, DOT

§ 153.1119

(ii) 60 mPa.s, if the cargo is a high viscosity Category C NLS.

[81-101, 53 FR 28975, Aug. 1, 1988 and 54 FR 12629, Mar. 28, 1989]

§ 153.1112 Prewash for tanks containing Category A NLS residue.

Unless § 153.1114 allows the prewash to be omitted, a cargo tank that unloads a Category A NLS cargo must be prewashed following the procedures in § 153.1120.

§ 153.1114 Conditions under which a prewash may be omitted: Categories A, B, and C.

A prewash required by this part may be omitted if one of the following requirements is met:

(a) A Surveyor has signed a statement in the Cargo Record Book that the next cargo has been determined to be one that may be loaded without washing the tank, and the tank is not washed or ballasted before it is loaded with the next cargo.

(b) A Surveyor has signed a statement in the Cargo Record Book that the approved Procedures and Arrangements Manual contains procedures for removing the NLS residue by ventilation, and the cargo tank is not washed or ballasted before being cleaned following the ventilation procedure.

NOTE: The Clean Air Act (42 U.S.C. 7401 *et seq.*) allows states to regulate emissions from tank ventilation. There may be other regulations, both local and Federal, that affect the use of tank ventilation for safety or environmental purposes.

(c) The tank requiring the prewash has a waiver issued under § 153.483 or § 153.491 and the waiver states when the tank is to be prewashed.

§ 153.1116 Prewash for tanks unloaded without following the approved Procedures and Arrangements Manual: Categories B and C.

If for any reason more Category B or C NLS residue remains in a cargo tank and transfer piping of a ship after unloading than would remain after a normal discharge of the cargo when the unloading procedures in the approved Procedures and Arrangements Manual are followed, the tank must be prewashed following the procedures in § 153.1120 unless—

(a) Section 153.1114 allows the prewash to be omitted; or

(b) The residue is reduced using another procedure, and a Surveyor estimates and states in the Cargo Record Book that the cargo tank and transfer piping contain no more NLS residue than they would if discharged following the procedures in the approved Procedures and Arrangements Manual, and no other prewash is required by this part.

§ 153.1118 Prewash of Categories B and C cargo tanks not meeting stripping standards: Categories B and C.

(a) Unless § 153.1114 allows the prewash to be omitted, a cargo tank from which a Category B NLS is unloaded must be prewashed using the procedures in § 153.1120(b) if the tank—

(1) Operates under the interim standard in § 153.481(b); or

(2) Has a waiver issued under § 153.483.

(b) Unless § 153.1114 allows the prewash to be omitted, a cargo tank from which a Category C NLS is unloaded must be prewashed using the procedures in § 153.1120(b) if the tank has a waiver issued under § 153.483.

§ 153.1119 When to prewash and discharge NLS residues from a prewash; unloading an NLS cargo in a country whose Administration is not signatory to MARPOL 73/78: Categories A, B, and C.

(a) Except as allowed in paragraphs (b), (c), and (e) of this section, each prewash required by this subpart must be completed and all tank washings must be discharged to a reception facility before the ship leaves the unloading port.

(b) NLS residue from the prewash following the unloading of a Category B NLS may be transferred to a slop tank for discharge under § 153.1126 instead of being discharged under paragraph (a) of this section if the prewash is required solely under § 153.1118(a)(1).

(c) A tank that is required by this part to be prewashed may be prewashed in a port other than the unloading port if the following conditions are met:

(1) The person in charge requests permission from the Commandant (G-MSO) (tel num; 202-267-1217) if the prewash port is a foreign port, or the